

1978 Franks 300 s/n 1287160DTD4519581

RIG 123

FRANKS 300 EXPLORER Mobile Double Class
III (4200m)

Rig Inventory

- Franks 300 Explorer Mobile Double Class 3
- Four axle, self-propelled, double drum, back in rig
- 4200 m x 73 mm tubing
- 12.7 liter 60 series Detroit Diesel rated at 425 hp engine
- Allison CLT-750 five speed transmission
- 30.5cm x 106.5cm main drum with 38.1 cm Parkersburg hydro brake
- 20.3cm x 106.5cm sand drum
- 31.1 Meters Franks 102-215 mast with a max load of 95,600 daN w/ 6 lines
- 4200m x 73mm tubing and 3000 m sucker rods
- Ideco 110 ton Shorty trave; blocks
- Fluorescent lighting
- 1" drilling line
- 4000 meters 12.7 mm swedge sand line
- Hydraulic weight indicator
- Dual winches

Combination

- 9 m x 2.6 m mobile combination building
- 4.4 m x 2.6 m tool house / accumulator portion
- John Deer 60 KW generator
- 2006 Sterling Acterra (tandem drive) w/ Cat C7 300 hp engine & Allison 3500RDS transmission

Handling Equipment

- 58-93R Foster tubing tongs
- Cavins TC 101 air slips
- BJ, Oil Country elevators
- 60.3 mm, 73 mm & 88.9 mm standard tubing sizes
- 5/8" and 1" rod sizes
- 2 - 8 x 42 and 2 - 6 x 16 rig mats
- Catwalk & 3 sets pipe racks

Safety Equipment

- 4 - 18 KG fire extinguishers
- 6 - Scott SCBA self-contained breathing apparatuses
- Industrial Scientific M-40 gas detector

- Safety and directional signs
- Electrical Ground Bonding Equipment
- Stretcher
- Crown Saver
- 60.3 mm, 73 mm & 88.9 mm pipe rams
- 1 self-retracting life lines

BOP Equipment

- Class III
- Schaffer 35 Mpa annular and Dreco 35 Mpa double-gate
- 166 liter T3 Oilco Model C1044311T3A accumulator with a pressure rating of 21Mpa, s/n 4005260
- 73 mm x 35 Mpa safety valve
- 76.2 mm rod BOP
- 76.2 mm x 6 m swab lubricator c/w tool trap
- 73 mm gate valve

Pump

- 2005 Capital Rig, tandem – tandem homemade rig carrier style
- 101.6 mm x 127 mm National JWS-340 triplex with a pressure rating of 35 Mpa
- Detroit Diesel 50 series rated at 350 hp engine
- Allison CLT-750 5 speed transmission
- 3 x 2 x 13Mission Magnum I charger pump
- 7 valve manifold with a pressure rating of 35 Mpa

Mud Tank

- 28 M3 mud tank c/w mud guns, mixing hopper and settling trough
- 20 - 5.08 cm X 6 m line pipe and suction hose
- Poor boy degasser
- External Gauge

